



Leírás Interruttore automatico scatolato

Cikkszám MSX 125

Pólusok száma 4P

Névleges

áramerősség 20 A

Kioldás Elettromeccanico


ELECTRICAL CHARACTERISTICS

Szabvány	IEC/EN 60947-2	Végrehajtás	Fisso - Rimovibile
Alkalmazási kategória	A	DIN rail mounting	Si, tramite accessorio
Névleges frekvencia	50 / 60	Accessoriabile con comando motore	Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever – Cable
Maximális feszültségimpulzus terhelhetőség (Uimp)	8 kV	Terminals supplied	FC előlapi csatlakozó terminál
Túlfeszültség kategória	IV	Szerelési pozíció	Bármely
Szigetelési feszültség (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	-	Electrical life (415Vac)	30.000 cycles
Magnetic regulation	6 - 8 - 10 - 12 x In	Mechanical life	30.000 cycles
Neutral protection	-	Üzemi hőmérséklet	-5°C +65°C
Total power loss	24 W	Tárolási hőmérséklet	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Súly (kg)	1.4
Rated short-time withstand current for 0,3s (Icw)	-	Szélesség	120 mm
I _{dn} regulation	-	Magasság	155 mm
DT regulation	-	Mélység	68 mm

SERVICE BREAKING CAPACITY (ICU)

Rated Voltage	Rated Breaking Capacity (ICU)	Rated Breaking Capacity (ICS)	Rated Breaking Capacity (ICS)
220/240Vac	50 kA	220/240Vac	50 kA
400/415Vac	36 kA	400/415Vac	36 / 30 kA
440Vac	25 kA	440Vac	25 kA
525Vac	22 kA	525Vac	22 kA
690Vac	6 kA	690Vac	6 kA
250Vdc	25 kA	250Vdc	19 kA

DIMENSIONAL





Product Data Sheet

GWD9211

MSX Sorozat

STANDARDS/APPROVALS

