



The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socket-outlets (with or without a fuse-holder) up to 63A, or socket-outlets type IEC 309.. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cable-fastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

סוג	Q-BOX 4	סוג לוח	ריק
צבע	תכלת	x גובהא מידות חיצוניות אורך (מ"מ) עומק	636x821x400
(ק"ג)משקל	16	לפי התקנים	EN 61439-4 (ACS)
מאפיינים	עמידות לאולטרה-סגול (EN 62208)	IP	IP55
זעזוע התנגדות	IK10	בדיקת תיל לוחט	650 °C
לחץ תרמי עם כדור	70 °C	classבידוד	II
קוד חשמלי	2241		

DIMENSIONAL

TECHNICAL SYMBOLOGY



IP


IP55

IK

IK10

GWT

650 °C



STANDARDS/APPROVALS

