





ELIA FL is a LED outdoor floodlight available in low, medium and high power versions for lighting external industrial areas, such as car parks and walkways or driveways. It can be mounted on surfaces, ceilings or on the ground using the adjustable steel bracket supplied with the device, or in the pole head version, courtesy of the dedicated accessory for poles with a diameter of up to 61mm. Crafted from black powder-coated die-cast aluminium, it is available in four sizes and powers, with integrated power supply in the On/Off or DALI options, three types of optic (30°, 60° and asymmetrical) with a colour temperature of 4,000K (neutral white) and a colour rendering index of more than 80. Tough and durable, ELIA FL has been designed to withstand surges of up to 10KV and temperature variations from -30 °C to + 50 °C, and offers protection from water and dust penetration of up to level IP66 and from shocks and impacts of up to level IK08. ELIA FL is quick and easy to install thanks to its limited weight and adjustable bracket.

מידע כללי	תכונות אופטיקה ותאורה	אסימטרי
הקשר	תעשייה, לוגיסטיקה, חזית, ספורט	-
גוף תאורה	גוף תאורה לד עם עוצמת לומן גבוהה ובינונית	-
יישום	חוץ/ פנים	24000
ייחודי (Datamatrix) קוד דיגיטלי	לא קיים כעת	130
צבע	שחור	3000 K
סוג מקור אור	לד	GRI 80
מערכת הספק	200 W	SDCM = 5
משך חייל	L80B50 (Tq25°) = 89.000h	RG12
משקל (ק"ג)	6.3	-
אחריות	5 שנים	-
טמפרטורת אחסון	-40° +85°	100-240 V
טמפרטורת עבודה	-30°C ÷ +50 °C	50/60 Hz
חומרים	-	כלול
גוף	אלומיניום יצוק	F10 = 80.000h Tq25°C
סוג סינכר	מ"מ עם לוגו של 4 זכוכית מחוסמת חלקה ושטוחה בעובי Gewiss	10-6kV הגנה מפני מתח יתר
אופטיקה	עם מערכת אופטית ביעילות גבוהה	פועל כבוי
אטם	-	-
קריסטל	-	התקנה על - התקנה על הקיר - עמודי תאורה גבוהים
בורג חיצוני	פלדת אל-חלד	התקנה על - התקנה על הקיר - עמודי תאורה גבוהים
צבע	ציפוי אבקה	עם תפס מתכוונן מורכב
תקנים ואישורים	-	עם כבל חשמל
סיווג	-	-
אביזר עם מופחת	-	על-ידי איש מקצוע
טמפרטורת פני שטח	-	על-ידי איש מקצוע
אישור DIN 18032-3	-	מובנה
IPEA	-	מ"ר 0.15
class	I	-
IP	IP66	-
דרגה	-	-
זעזוע התנגדות	IK08	-
בדיקת חום	750 °C	-

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



### TECHNICAL SYMBOLOGY





Product Data Sheet  
**GWF1100VC830**

ELIA FL

STANDARDS/APPROVALS

