



Flush-mounting roller shutter touch module. Device for commanding the motor that drives roller shutters, curtains, Venetian blinds, roller blinds, etc. via 2 interlocked output contacts with potential. There are two frontal touch areas for upward (UP) and downward (DOWN) movement, and for regulating the tilt of the slats. The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol. The device has n°3 DIP-switches, located on the back of the device, for feature configuration.

Descriere	Touch roller-shutter module	Alimentare electrică	100 ÷ 240 V c.a. - 50/60 Hz
Nr. module	1	Nr. canale de intrare	2
Comandă locală	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Tensiune canal intrare auxiliară	100 ÷ 240 V c.a. - 50/60 Hz
Temperatura de stocare	-25 ÷ +70 °C	Nr. canale de ieșire	2
Temperatura de lucru	-5 ÷ +45 °C	Contacte ieșire	n. 2 x 2,3 A cosφ 0,6
Umiditate relativă (necondensată)	Max. 93%	Lămpi cu halogen incandescent de 240 V c.a.	-
Semnalizare cu lumină frontală	LED albastru	Lămpi LED de 240 V c.a.	-
Borne de cablare	Conținut	Sarcini pilotate de la transformatoare electronice 240 V c.a.	-
Capacitate de strângere borne cabluri torsadate (mm ²)	Max 1,5	Lămpi fluorescente de 240 V	-
Capacitate de strângere a bornelor cabluri solide (mm ²)	Max 1,5	Controlul sarcinii	-
Context	Dry indoor places	Acoustic signalling element	Buzzer
Grad IP	IP20 (with plate fitted)	Standard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

