



Flush-mounting touch switch module. Two touch areas on the front for switching an ON/OFF load (bistable/momentary function) or a timed ON load via an output contact with potential. The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol. The device has N°3 DIP-switches, located on the back of the device, for feature configuration.

| | | | |
|--|--|---|--|
| Descriere | Înterupător unidirecțional tactil | Alimentare electrică | 100 ÷ 240 V c.a. - 50/60 Hz |
| Nr. module | 1 | Nr. canale de intrare | 2 |
| Comandă locală | Via 2 frontal touch areas (must be completed with ICE Touch plate) | Tensiune canal intrare auxiliară | 100 ÷ 240 V c.a. - 50/60 Hz |
| Temperatura de stocare | -25 ÷ +70 °C | Nr. canale de ieșire | 1 |
| Temperatura de lucru | -5 ÷ +45 °C | Contacte ieșire | 1 NA 5A (AC1) 240 V ca |
| Umiditate relativă (necondensată) | Max. 93% | Lămpi cu halogen incandescent de 240 V c.a. | Max 1000 W |
| Semnalizare cu lumină frontală | LED albastru | Lămpi LED de 240 V c.a. | Max 100 W (max 5 lamps) |
| Borne de cablare | Conținut | Sarcini pilotate de la transformatoare electronice 240 V c.a. | Max 250 VA |
| Capacitate de strângere borne cabluri torsadate (mm ²) | Max 1,5 | Lămpi fluorescente de 240 V | Max 120 W (max 6 lamps) |
| Capacitate de strângere a bornelor cabluri solide (mm ²) | Max 1,5 | Controlul sarcinii | - |
| Context | Dry indoor places | Acoustic signalling element | Buzzer |
| Grad IP | IP20 (with plate fitted) | Standard | 2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000 |

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

