# Product Data Sheet

## GW10677

CHORUSMART - Gama de produse de uz casnic

Flush-mounting axial auxiliary module with one command. An axial push-buttons on the front; this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, EVO commands, or as a wired command for a connected 2-channel ZigBee interface. The module with 1 auxiliary axial command can also be used to directly command small resistive or weakly inductive loads such as ringers and buzzers (max. 10VA);.
The device must be completed with one of the front buttons key available.

| | | | |
|---|---|---|---|
| **Descriere** | **Comandă axială auxiliară cu 1 canal** | **Alimentare electrică** | **100 ÷ 240 V c.a. - 50/60 Hz** |
| **Nr. module** | **1** | **Nr. canale de intrare** | **-** |
| **Comandă locală** | **Prin intermediul butonului frontal (pentru a finaliza cu tasta buton)** | **Tensiune canal intrare auxiliară** | **-** |
| **Temperatura de stocare** | **-25 ÷ +70 °C** | **Nr. de canale de intrare LED** | **1** |
| **Temperatura de lucru** | **-5 ÷ +45 °C** | **Tensiunea canalelor de intrare LED** | **100 ÷ 240 V c.a. - 50/60 Hz** |
| **Umiditate relativă (necondensată)** | **Max. 93%** | **Nr. canale de ieşire** | **1** |
| **Semnalizare cu lumină frontală** | **LED albastru** | **Contacte ieşire** | **1A (AC1)** |
| **Borne de cablare** | **Conținut** | **Lămpi cu halogen incandescent de 240 V c.a.** | **-** |
| **Capacitate de strângere borne cabluri torsadate (mm²)** | **Max 1,5** | **Lămpi LED de 240 V c.a.** | **-** |
| **Capacitate de strângere a bornelor cabluri solide (mm²)** | **Max 1,5** | **Sarcini pilotate de la transformatoare electronice 240 V c.a.** | **-** |
| **Context** | **Dry indoor places** | **Lămpi fluorescente de 240 V** | **-** |
| **Grad IP** | **IP20 (cu buton)** | **Controlul sarcinii** | **-** |
| **Standard** | **2014/35/EU (LVD), 2011/65/EU + 2015/863 (RoHS), EN 60669-1, EN IEC 63000** | | |

## DIMENSIONAL







## TECHNICAL SYMBOLOGY

**IP**

IP20 (cu buton)

## STANDARDS/APPROVALS

UK CA CE

GEWISS S.p.A. Via Domenico Bosatelli 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 12/10/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice