




Descrizione Interruttore automatico scatolato
 Cod MSX 160c
 Nr. poli 3P
 Curent nominal 25 A
 Eliberare Elettromeccanico

ELECTRICAL CHARACTERISTICS		- MECHANICAL CHARACTERISTICS	
Standard	IEC/EN 60947-2	Executare	Fix
Categoria de utilizare	A	DIN rail mounting	Si, tramite accessorio
Frecvență nominală (Hz)	50 / 60	Accessoriabile con comando motore	Nu
Rated operating voltage (Ue)	525 Vac - 250 Vdc	Compatible interlock	-
Tensiune nominală de rezistență la impulsuri (Uimp)	8 kV	Terminals supplied	Față pentru cabluri FW
Categorie supratensiune	IV	Poziția de asamblare	Orice
Tensiune de izolare (Ui)	690 V	Upline/downline power supply	Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	14.000 cicli
Magnetic regulation	Fisso - 600A	Mechanical life	20.000 cicli
Neutral protection	-	Temperatură de funcționare	-5°C +65°C
Total power loss	13.8 W	Temperatura de stocare	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Greutate (kg)	0.8
Rated short-time withstand current for 0,3s (Icw)	-	Lățime	75 mm
I _{dn} regulation	-	Înălțime	130 mm
DT regulation	-	Adâncime	68 mm
SERVICE BREAKING CAPACITY (ICU)		- RATED BREAKING CAPACITY (ICS)	
220/240Vac	25 kA	220/240Vac	13 kA
400/415Vac	16 kA	400/415Vac	8 kA
440Vac	10 kA	440Vac	5 kA
525Vac	6 kA	525Vac	3 kA
690Vac	-	690Vac	-
250Vdc	13 kA	250Vdc	7 kA

DIMENSIONAL





Product Data Sheet

GWD9001

Gama MSX

STANDARDS/APPROVALS

