




Descrizione Interruttore automatico scatolato
 Cod MSX 125
 Nr. poli 3P
 Curent nominal 100 A
 Eliberare Elettromeccanico

ELECTRICAL CHARACTERISTICS

Standard	IEC/EN 60947-2	MECHANICAL CHARACTERISTICS	Executare	Fisso - Rimovibile
Categoria de utilizare	A	DIN rail mounting		Si, tramite accessorio
Frecvență nominală (Hz)	50 / 60	Accessoriabile con comando motore		Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock		Lever – Cable
Tensiune nominală de rezistență la impulsuri (Uimp)	8 kV	Terminals supplied		Front FC
Categorie supratensiune	IV	Poziția de asamblare		Orice
Tensiune de izolare (Ui)	800 V	Upline/downline power supply		Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)		30.000 cycles
Magnetic regulation	6 - 8 - 10 - 12 x In	Mechanical life		30.000 cycles
Neutral protection		Temperatură de funcționare		-5°C +65°C
Total power loss	24 W	Temperatura de stocare		-20° +65°
Rated short-circuit current making capacity (Icm)		Greutate (kg)		1.1
Rated short-time withstand current for 0,3s (Icw)		Lățime		90 mm
I _{dn} regulation		Înălțime		155 mm
DT regulation		Adâncime		68 mm
SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)		
220/240Vac	50 kA	220/240Vac		50 kA
400/415Vac	36 kA	400/415Vac		36 / 30 kA
440Vac	25 kA	440Vac		25 kA
525Vac	22 kA	525Vac		22 kA
690Vac	6 kA	690Vac		6 kA
250Vdc	25 kA	250Vdc		19 kA

DIMENSIONAL





Product Data Sheet

GWD9125

Gama MSX

STANDARDS/APPROVALS

