




Descriere Interruttore automatico scatolato
 Cod MSX 125
 Nr. poli 4P
 Curent nominal 125 A
 Eliberare Electromechanic

ELECTRICAL CHARACTERISTICS		MECHANICAL CHARACTERISTICS	
Standard	IEC/EN 60947-2	Executare	Fixed - Plug-in
Categoria de utilizare	A	DIN rail mounting	Yes, by means of accessory
Frecvență nominală (Hz)	50 / 60	Can be equipped with motor operator	Yes
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever – Cable
Tensiune nominală de rezistență la impulsuri (Uimp)	8 kV	Terminals supplied	Front FC
Categorie supratensiune	IV	Poziția de asamblare	Orice
Tensiune de izolare (Ui)	800 V	Upline/downline power supply	Yes
Thermal regulation	-	Electrical life (415Vac)	30.000 cycles
Magnetic regulation	6 - 8 - 10 x In	Mechanical life	30.000 cycles
Neutral protection	-	Temperatură de funcționare	-5°C +65°C
Total power loss	39.36 W	Temperatura de stocare	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Greutate (kg)	1.4
Rated short-time withstand current for 0,3s (Icw)	-	Lățime	120 mm
I _{dn} regulation	-	Înălțime	155 mm
DT regulation	-	Adâncime	68 mm
SERVICE BREAKING CAPACITY (ICU)	-	RATED BREAKING CAPACITY (ICS)	-
220/240Vac	50 kA	220/240Vac	50 kA
400/415Vac	36 kA	400/415Vac	36 / 30 kA
440Vac	25 kA	440Vac	25 kA
525Vac	22 kA	525Vac	22 kA
690Vac	6 kA	690Vac	6 kA
250Vdc	25 kA	250Vdc	19 kA

DIMENSIONAL





Product Data Sheet

GWD9216

Gama MSX

STANDARDS/APPROVALS

