





Wide range of surface-mounting and flush-mounting boxes for domestic ranges with high mechanical robustness and accessories supplied: dividers, junction elements, mortarguard shield, etc. Completing the range, the distribution outlet boxes for floor-mounting installations can be personalised in terms of capacity, external design finish, and internal fittings (they take both System range components and DIN rail devices).

Nr. bande	3 module	Grad de protecție IP	IP40
Tip	Pentru pereți de zidărie	Test de încercare cu fir incandescent	650 °C
Categorie	Pentru gama casnică	Termo-presiune cu bilă	70 °C
Conformitate cu standardele	EN 60670-1 (CEI 23-48)	Dim. exterioară LxHxD (mm)	119x80x50
Material	Tehnopolimer GW PLAST	Distanță axe suporturi de fixare	83.5 mm
- Fără halogen	Fără halogeni în conformitate cu EN 60754-2	Intrări cablu	2 x Ø 20/25 + 10 x Ø 20/25 cut-outs
Culoare	Portocaliu RAL 2001	Tip de predecupaje	Demontabil cu unealtă
Temperatura de instalare	-15 +60 °C		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY

GWT

650 °C



70 °C

HF

Fără halogeni în conformitate cu EN 60754-2

STANDARDS/APPROVALS

