



Category ChoruSmart series

Type Command devices



Group DIN rail KNX actuators

Category ON / OFF

Communication KNX Secure

No. DIN modules	4	Power supply	Via KNX BUS, 29 V DC SELV
Interfaces	KNX TP1	Current absorbed by KNX bus (mA)	Max 10 mA a 29 V
Dispersible power (W)	4	No. output channels	4
Output contacts	4 NA 16 AX 230 V ac	Wiring terminals	With screw
Terminal tightening capacity stranded cables (mm ²)	Max 4 mm ²	Connection to the KNX bus	KNX bus terminal
240 V ac Incandescent-halogen lamps	3000 W	Loads controlled from toroidal transformers	3000 W
Loads controlled from electronic transformers	2000 W	230V LED lamps	400 W
Working temperature	-5 ÷ +45 °C	Stocking temperature	-25 ÷ +55 °C
IP degree	IP20	Standard	RoHS Directive 2011/65/EU+2015/863 - EN IEC 63000 Low Voltage Directive 2014/35/EU_x000D_; Electromagnetic Compatibility Directive 2014/30/EU EN 60669-2-1

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 26/07/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice