





The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

<b>INPUT</b>			- Socket/Connector Nr. (Type)	2 (Type 2 vandal-proof socket, with shutters)
Terminal blocks	2 x (5 x 10 mm <sup>2</sup> )	Charging activation	Remotely managed, via OCPP 1.6J	
Rated current	64 A	Human Interface	LED RGB and TFT Display	
Total power	44 Kilowatt	Connectivity	LAN	
<b>OUTPUT</b>			- <b>MECHANICAL FACTS</b>	-
Rated voltage	400 V	Mounting and installation	Wall mount	
Colour	Grey, Headboard RAL 7011	Power max.	22 kW per socket	
Material	Steel sheet	Thermal-magnetic protection	Currently not present	
External treatments	Anti-corrosion and anti-graffiti	Type of residual current protection	Currently not present	
IP degree	IP55	Power meter	Yes (Type MID)	
Mechanical resistance	IK10	DC Leakage check	Currently not present	
Operating temperature	-25 +50 °C	(Auto)restart electrical protections	Currently not present	
Customizations	Yes (front)			

### DIMENSIONAL



### TECHNICAL SYMBOLOGY

**IP**

**IK**

IP55

IK10

### STANDARDS/APPROVALS

