



Product Data Sheet GW10213 CHORUSMART - Domestic range





Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The ChoruSmart modular devices are available in five colours, glossy white, satin white, natural beige, satin black and lacquered titanium and in various sizes from 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the ChoruSmart range of plates.

Category	Dual amperage socket-outlet	Description	2P+E - 16 A Dual amperage
Colour	Red	Туре	for dedicated lines
Voltage	250 V ac	Standard	English
Characteristics	With safety shields	For plug pins	Ø 4 / 5 mm
Wiring terminals	With screw	Socket-out type	P11-P17
Standard	CEI 23-50	Resistance at test voltage	2000 V at 50 Hz for 1 minute
Insulation resistance	> 5 MOhm	Prolonged operation socket (no.of position changes)	10.000 at In 250 V ac cosφ=0,8
Thermo-pressure with ball	125 °C	Glow Wire Test	850 °C
Terminal grip on cable traction	> 50 N	Terminal tightening capacity	min. 0,75 - max. 2x4
		stranded cables (mm ²)	
Terminal tightening capacity	min. 0,5 - max. 2x2,5	No. modules	1
solid cables (mm²)			
Electrocod	0131	Material	Technopolymer



DIMENSIONAL





TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

