




USB C charger, for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones and smart watches. Charging compatibility with devices on the market is guaranteed by USB-IF certification.

Category	USB power supply	Supply voltage	100 ÷ 240 V ac - 50/60 Hz
Voltage	0,6 A max	Wiring terminals	With screw
Terminal tightening capacity solid cables (mm <sup>2</sup> )	min. 1 - max. 1,5 mm <sup>2</sup>	Terminal tightening capacity stranded cables (mm <sup>2</sup> )	min. 1 - max. 1,5
Max. total power output	30 W	Outputs/N° and type	1 / C
No-load power (W)	< 0,075 W	Working temperature	0 ÷ +40 °C
Stocking temperature	-25 ÷ +85 °C	IP degree	IP20
Relative humidity (non-condensative)	Max 93%	Technology	Power Delivery - PPS
Protection integrated	Overcurrent, overvoltage, overtemperature, short circuit, derating, auto recovery mode	Colour	Glossy white
No. modules	1	Material	Technopolymer
Standard	EN IEC 62368-1, EN 55032, EN 55035, EN IEC 61000-3-2, EN 61000-3-3, EN IEC 62680		

### DIMENSIONAL



### TECHNICAL SYMBOLOGY

**IP**

IP20

### STANDARDS/APPROVALS

