



USB C charger, fast charging up to 63W with Power Delivery technology.




Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools.

Power sharing between the two ports is dynamically managed, automatically optimizing the energy supplied between connected devices to ensure efficient and safe charging at all times.

Charging compatibility with market devices is guaranteed by USB-IF certification.

Category	USB power supply	Supply voltage	100 ÷ 240 V ac - 50/60 Hz
Voltage	1.4 A max	Wiring terminals	With screw
Terminal tightening capacity solid cables (mm ²)	min. 1 - max. 1.5 mm ²	Terminal tightening capacity stranded cables (mm ²)	min. 1 - max. 1.5
Max. total power output	63 W	Outputs/N° and type	2 / C
No-load power (W)	< 0.15 W	Working temperature	0 ÷ +40 °C
Stocking temperature	-25 ÷ +85 °C	IP degree	IP20
Relative humidity (non-condensative)	Max 93%	Technology	Power Delivery - PPS
Protection integrated	Overcurrent, overvoltage, overtemperature, short circuit, derating, auto recovery mode	Colour	Glossy white
No. modules	2	Material	Technopolymer
Standard	EN IEC 62368-1, EN 55032, EN 55035, EN IEC 61000-3-2, EN 61000-3-3, EN IEC 62680		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 24/10/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice