




A complete range of commands and protections, energy and signal sockets, temperature control units, comfort management solutions, and acoustic/visual signalling devices. The commands, available with two different buttons designs, are illuminated with LED light and feature elegant indicator icons. System Pura is available in two colours and two finishes: glossy white, satin black and satin white. The series proposes intuitive and modern solutions designed to enhance any space. These features make it ideal for both residential applications and special installations, where reliability and aesthetics must coexist harmoniously.

|                                                 |                              |                                                      |                                              |
|-------------------------------------------------|------------------------------|------------------------------------------------------|----------------------------------------------|
| Category                                        | One-way switch               | Button key                                           | With symbol                                  |
| Symbol                                          | 0/1                          | Description                                          | 25 A                                         |
| Colour                                          | Glossy white                 | Voltage                                              | 250 V ac                                     |
| Signalling unit                                 | -                            | Standard                                             | EN 60669-1                                   |
| Resistance at test voltage                      | 2000 V at 50 Hz for 1 minute | Insulation resistance                                | > 5 MOhm                                     |
| Wiring terminals                                | With screw                   | Prolonged operation switch (no. of position changes) | 10.000 at In 250 V ac cosφ=0.6               |
| Thermo-pressure with ball                       | 125 °C                       | Glow Wire Test                                       | 850 °C                                       |
| Terminal grip on cable traction                 | > 50 N                       | Terminal tightening capacity stranded cables (mm²)   | min. 0.75 - max. 2x4                         |
| Terminal tightening capacity solid cables (mm²) | min. 0.5 - max. 2x2.5        | No. modules                                          | 1                                            |
| Material                                        | Technopolymer                | Halogen Free                                         | Halogen-free in compliance with EN IEC 63355 |
| Type of use                                     | Heavy duty                   | Electrocod                                           | 0130                                         |

## DIMENSIONAL



## TECHNICAL SYMBOLOGY



## STANDARDS/APPROVALS

