






A complete range of commands and protections, energy and signal sockets, temperature control units, comfort management solutions, and acoustic/visual signalling devices. The commands, available with two different buttons designs, are illuminated with LED light and feature elegant indicator icons. System Pura is available in two colours and two finishes: glossy white, satin black and satin white. The series proposes intuitive and modern solutions designed to enhance any space. These features make it ideal for both residential applications and special installations, where reliability and aesthetics must coexist harmoniously.

Category	Relay	Description	For call
Colour	Satin black	LED colour	White
Output contacts	1NO/NC 12 V (max. 1 A)	No. of poles	1
Voltage	12 V ac/dc	Standard	EN 60669-1 / EN 60669-2-2
Resistance at test voltage	2000 V at 50 Hz for 1 minute	Insulation resistance	> 5 MOhm
Wiring terminals	With screw	Prolonged operation switch (no. of position changes)	40.000 at In 250 V ac cosφ=0.6
Thermo-pressure with ball	125 °C	Glow Wire Test	850 °C
Terminal grip on cable traction	> 50 N	Terminal tightening capacity stranded cables (mm ²)	min. 0.75 - max. 2x4
Terminal tightening capacity solid cables (mm ²)	min. 0.5 - max. 2x2.5	No. modules	1
Electrocod	140		

DIMENSIONAL



TECHNICAL SYMBOLOGY



GWT

125 °C

850 °C

STANDARDS/APPROVALS

