




The IP40 protected flush mounting enclosures are available in sizes from 8 to 72M and are equipped with screw multipolar terminal blocks, 80 A IP 20. They are available with a smoked transparent door (particularly suitable for the commercial and industrial sector) or a blank door (ideal for domestic application); the terminal blocks allow to create simple and neat wiring reducing the set-up time of the enclosure.

Insulation class	II (according to IEC 61140 standards)		Colour	White RAL 9016
Outer dim. LxHxD (mm)	465x310x85		IP degree	IP40
Installation	For brick wall		Dispersible power (W)	50
Mechanical resistance	IK08		Rated voltage	400 V
Door colour	Blank		Terminal blocks	80 A - IP20 bipolar holes with screws
No. of modules EN 50022	18		Rated current	125 A
Glow Wire Test	650 °C		Operating temperature	-15 ÷ +60°C
Type of material	Halogen-free in compliance with EN 60754-2			
Thermo-pressure with ball	70 °C		Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49
Insulation voltage	750 V		Pole 1 (mm ²)	N/E (3x16) + (17x10)
Pole 2 (mm ²)	N/E (3x16) + (17x10)			

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Not resistant	Limited resistance	Resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY



II (according to IEC 61140 standards)

IP

IP40


IK

IK08

GWT

650 °C

INSTALLATION



-15 ÷ +60°C

HF

HALOGEN FREE

Halogen-free in compliance with EN 60754-2



70 °C

STANDARDS/APPROVALS

