

Product Data Sheet GW10007AB

CHORUSMART - Domestic range




A range of ChoruSmart modular devices and plates made of antibacterial technopolymer in a glossy white finish, suitable for use in hospitals, nursing homes, schools and wherever cleanness and hygiene are essential. The effective silver-ion antibacterial treatment can reduce bacterial growth by 99% within 24 hours and has been verified by certified laboratory testing in accordance with standard ISO 22196 (analysis of major strains of Staphylococcus aureus and E. coli bacterial species).

Category	One-way switch	Type of use	Heavy duty
Colour	Glossy white	Description	2P - 25 AX
Voltage	250 V ac	Standard	EN 60669-1; ISO 22196
Resistance at test voltage	2000 V at 50 Hz for 1 minute	Rated power of 230V LED lamps	250 W
Insulation resistance	> 5 MOhm	Wiring terminals	With screw
Prolonged operation switch (no.of position changes)	40.000 at ln 250 V ac $\cos\varphi$ =0,6	Thermo-pressure with ball	125 °C
Glow Wire Test	850 °C	Terminal grip on cable traction	> 50 N
Terminal tightening capacity	min. 0,75 - max. 2x4	Terminal tightening capacity	min. 0,5 - max. 2x2,5
stranded cables (mm ²)		solid cables (mm ²)	
No. modules	1	Button key	Neutral
Symbol	0/1	Material	Antibacterial tecnopolymer
Electrocod	0130		


1.95

3.7



DIMENSIONAL





TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS



www.gewiss.com sat@gewiss.com Last update 10/05/2025 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice