



No. DIN modules 4

Supply voltage 12-24 V dc

No. input channels 4

Input channel type Comando per LED CVD

Type of output loads 4 uscite per LED CVD, pilotate dal dimmer CVD collegato. Pilotaggio carico ad anodo comune

No. output channels	4	Max current per channel	16 A
Rated power	768 W max. a 12Vdc - 1536 W max. a 24Vdc	Dispersible max power (W)	6 W
Max power supply cable length (m)	3 m	Wiring terminals	With screw
Terminal tightening capacity stranded cables (mm ²)	Max. 4	Working temperature	-5 ÷ +45 °C
Stocking temperature	-25 ÷ +55 °C	IP degree	IP20
Relative humidity (non-condensative)	Max 93%	Standard	Low Voltage Directive 2014/35/EU - Electromagnetic Compatibility Directive 2014/30/ EU - EN50428, EN50090-2-2

DIMENSIONAL

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 28/07/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice