



The KNX GWA9703 power supply is a 1280 mA DIN rail power supply, offering high efficiency and a compact footprint of just 4 DIN modules (72 mm). The device is equipped with an output with KNX bus inductance and an additional output for auxiliary power supply. LED indicators signal normal operation, overload conditions, and RESET operation.

Description	Supply unit	Communication	KNX
Connection to the KNX bus	KNX bus terminal	No. DIN modules	4
Power supply	180 ~ 264 V AC / 176 ~ 280 V DC (47 ~ 63Hz)	Output voltage	30 V dc +/- 2 V (SELV)
Current supplied (max)	1280 mA	Nominal output power (W)	38.4 W
Wiring terminals	With screw	Terminal tightening capacity stranded cables (mm <sup>2</sup> )	Max. 2,5
Working temperature	-30 ÷ +70 °C	Stocking temperature	-40 ÷ +85°C
IP degree	IP20	Relative humidity (non-condensative)	Max 93%
Standard	EN IEC 61558-1:2019, EN 61558-2-16:2009+A1:2013, EN50491-5-2:2010, EN 50491-5-3:2010, EN IEC 63044-5-2:2019, EN IEC 63044-5-3:2019		

### DIMENSIONAL



### TECHNICAL SYMBOLOGY

**IP**

IP20

### STANDARDS/APPROVALS

