



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.

The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.


ELECTRICAL CHARACTERISTICS

	Rotary isolator	Version	Enclosed
Circuit breaker	40	Material	Aluminium
Rated current (A)	2P	Type	Control
No. of poles	690	Knob colour	Black
Rated insulation voltage U_i (Vac)	40	Lockable	Yes (max. 3 padlocks in ON and OFF)
Rated operational current AC-21A (415 V) (A)	40	IP degree	IP66/IP69
Rated operational current AC-22A (415 V) (A)	40	Mechanical resistance	IK11 (enclosure); IK08 (knob)
Rated operational current AC-23A (415 V) (A)	10	Operating temperature	-25 +60 °C
Conditional short circuit current I_{cc} (415 V) (kA)	1-10 mm ²	Cable entries on top	1 x M20 + 1 x M25 + 2 x M16 max drilling points (E)
Cable section	-	Cable entries on bottom	1 x M20 + 1 x M25 + 2 x M16 max drilling points (E)
ACCESSORIES	-	Cable entries on back	2 x M25 max drilling points
Type of accessory	Max. 2 auxiliary contacts (1 per side)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Limited resistance	Limited resistance	Limited resistance	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IK

IP66/IP69

IK11 (enclosure);
IK08 (knob)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polfin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 28/07/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice