




Systems of accessories for electrical installations used for residential, tertiary and industrial applications. The system consists of fasteners for pipes and cables, cable fittings, accessories for rigid pipes (RK Series) and flexible conduit (DF Series). The system include also a wide variety of cable ties (52FS Range) and terminal blocks (44 Range).

IP degree	IP68 (at 10 bar)	Material	Nickel-plated brass
For cables Ø (mm)	from 6 to 10	Description	Cable gland
Type of pitch	M16	Mounting hole Ø (mm)	16
Area	1 (G) - 20 (D)	Electrocod	230
Ambient temperature	-60 °C ≤ Ta ≤ +95 °C	Standard	EN 50262 - IEC 62444 - EN 60079-0 - EN60079-7 - EN 60079-31 - EN 60079-7 - EN 60079-31 - IEC/EN 600243
Installation temperature	-20 +95 °C	ATEX Classification	2G 1D Ex e II tD A20 IP68

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant


DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP68 (at 10 bar)



-20 +95 °C

STANDARDS/APPROVALS

