


Cable ties, made in PA66, Halogen Free. Available in 13 sizes, from 2.4x75 to 9x914mm. To complete the series are available also: heavy duty wiring ties, re-openable cable ties, cable ties with eyelet and cable ties with plate.

Colour	Colourless	Dimensions LxH (mm)	2.5x110
Hole dimensions (mm)	4.8	Material	Polyamide 66
Tensile stress (daN)	8	Terminal grip capacity Ø	3-23 mm
Glow Wire Test	650 °C	Type	With eyelet
Type of material	Halogen-free in compliance with EN 60754-2	Electrocod	3640
Standard	EN 62775	Fume corrosiveness	< 5%
Flame resistance in compliance with UL 94	V2	Installation temperature	-5 +60 °C
Service temperature range	-40 °C +80 °C (max.peaks 135 °C)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Limited resistance	Limited resistance	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY


GWT

650 °C

HF

HALOGEN FREE

Halogen-free in compliance with EN 60754-2



INSTALLATION
-5 +60 °C

STANDARDS/APPROVALS

