





Floodlight in die cast aluminum with galvanized bracket and painted the same color as the body. Equipped with graduate scale to facilitate orientation. Separated optical and electrical compartment. Front opening through manual hooks. Flat tempered glass 5mm thickness. Anti-aging silicone gasket. Power input through cable camp for cables Ø 7 ÷ 10.5 mm. Optic in 99.85% polished and anodised aluminium. Electrical componentent plate in galvanized steel. Tripolar terminal block. To be completed with power supply.

| | | | |
|--------------------------------------|----------|--|---------------------------------|
| Application | External | IP degree | IP66 |
| Mechanical resistance | IK10 | Insulation class | I |
| Maximum surface exposed to the wind | 0.15 m² | Minimum distance from the illuminated object | 3 m |
| Weight (kg) | 9 | Colour | Graphite grey |
| Lamp | ST | Lamp power | 600 W |
| Lamp current | 6.2 A | Lamp holder | E40 |
| Efficiency class of compatible lamps | A+ ÷ A++ | Optic | Symmetrical diffused - ULOR: 0% |
| Electrocod | 244B | | |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP
IP66

IK
IK10



0.15 m²

3 m



STANDARDS/APPROVALS

