



Floodlight in die cast aluminum with galvanized bracket and painted the same color as the body. Equipped with graduate scale to facilitate orientation. Separated optical and electrical compartment. Front opening through manual hooks. Flat tempered glass 5mm thickness. Anti-aging silicone gasket. Power input through cable camp for cables Ø 7 ÷ 10.5 mm. Optic in 99.85% polished and anodised aluminium. Electrical componentent plate in galvanized steel. Tripolar terminal block. Wired version with power factor correction.

Application	External	IP degree	IP66
Mechanical resistance	IK10	Insulation class	I
Maximum surface exposed to the wind	0.15 m²	Minimum distance from the illuminated object	1 m
Weight (kg)	12.2	Colour	Graphite grey
Voltage	230 V - 50 Hz	Lamp power	400 W
Lamp current	4.2 A	Lamp holder	E40
Lamp supplied	MT	Lamp included	Yes
Efficiency class of the lamp supplied	A	Efficiency class of compatible lamps	A ÷ A+
Optic	Asymmetrical restricted - ULOR: 0%	Electrocod	244B

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP66

IK

IK10



0.15 m²



1 m



WITH LAMP



STANDARDS/APPROVALS

