





Floodlight in die cast aluminum with electrolytic galvanized bracket and painted the same color as the body  
Equipped with graduate scale to facilitate orientation Separated optical and electrical compartment Front opening through screws, lamp changing from back screwed door Flat tempered glass 5mm thickness Anti-aging silicone gasket Power input through PG13.5 for cables Ø 6.5 ÷ 13 mm Safety relay input via PG 11 for cables with diameter 7 ÷ 10 mm Optic in 99.85% polished and anodised aluminium Electrical componentent plate in galvanized steel Tripolar terminal block Wired version with power factor correction to be used with relative supply unit

Application	External	IP degree	IP66
Mechanical resistance	IK09	Insulation class	I
Maximum surface exposed to the wind	0.25 m²	Lateral surface exposed to the wind	0.083 m²
Minimum distance from the illuminated object	3 m	Weight (kg)	15.7
Colour	Graphite grey	Lamp	MT*
Lamp power	1000 W	Lamp current	8.25 A
Lamp holder	E40	Optic	Symmetrical diffused - ULOR: 0%
DIN 18032-3 certification	Compliant	Electrocod	2433

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP  
IP66

IK  
IK09



0.25 m²

3 m



STANDARDS/APPROVALS

