





Thermoplastic outdoor floodlight in smoke grey color with hot galvanized bracket painted the same color of the body. Equipped with graduate scale to facilitate orientation. Flat tempered glass 4 mm thickness silk screen printed; hinged to the body for quick access inside the floodlight. Anti-aging silicone gasket. Power input through PG 13,5 for cables Ø 6.5 ÷ 13 mm. Optic in 99.85% polished and anodized aluminium. Electrical component plate in galvanized steel. Bipolar terminal block for cable 4 mm².

| | | | |
|--|------------------------|--------------------------------------|----------------------|
| Application | External | IP degree | IP65 |
| Mechanical resistance | IK09 | Insulation class | II |
| Glow Wire Test | 650 °C | Maximum surface exposed to the wind | 0.124 m² |
| Minimum distance from the illuminated object | 1 m | Weight (kg) | 4.3 |
| Colour | Smoke grey | Voltage | 220-240 V - 50/60 Hz |
| Lamp | FSM | Lamp power | 2x26/32/42 W |
| Lamp holder | GX24q-3 / GX24q-4 | Efficiency class of compatible lamps | A |
| Driver type | EVG electronic reactor | Optic | Symmetrical |
| Light pollution | 0 cd/Klm | Warranty | 5 years |
| Electrocod | 2443 | | |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP
IP65

IK
IK09



GWT
650 °C



0.124 m²



1 m



STANDARDS/APPROVALS

