





Thermoplastic outdoor floodlight in smoke grey color with hot galvanized bracket painted the same color of the body. Equipped with graduate scale to facilitate orientation. Flat tempered glass 4 mm thickness silk screen printed; hinged to the body for quick access inside the floodlight. Anti-aging silicone gasket. Power input through PG 13,5 for cables Ø 6.5 ÷ 13 mm. Optic in 99.85% polished and anodized aluminium. Electrical component plate in galvanized steel. Bipolar terminal block for cable 4 mm².

Application	External	IP degree	IP65
Mechanical resistance	IK09	Insulation class	II
Glow Wire Test	650 °C	Maximum surface exposed to the wind	0.124 m²
Minimum distance from the illuminated object	1 m	Weight (kg)	4.3
Colour	Smoke grey	Voltage	220-240 V - 50/60 Hz
Lamp	FSM	Lamp power	2x26/32/42 W
Lamp holder	GX24q-3 / GX24q-4	Efficiency class of compatible lamps	A
Driver type	EVG electronic reactor	Optic	Symmetrical
Light pollution	0 cd/Klm	Warranty	5 years
Electrocod	2443		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP
IP65

IK
IK09



GWT
650 °C



0.124 m²



1 m



STANDARDS/APPROVALS

