




Street lighting in die-cast aluminium painted with polyester powders after trivalent passivation. The pole coupling base can be tilted for whip pole or pole head installation. Made of die-cast aluminium painted with polyester powders (grey graphite) after trivalent passivation. Equipped with graduated goniometric scale to facilitate pointing operations. Possibility of continuous regulation $\pm 20^\circ$ installation on side bracket; $0\text{--}20^\circ$ pole head installation. Optic in 99.85% polished and anodised aluminium. Anti-aging silicone gasket. Plastic bleed and anti-condensation device. Case containing electric components. Made of completely removable polyamide and equipped with a handle to facilitate assembly/disassembly operations and transport. Bipolar power supply terminal in double insulation for 2.5 mm² cables; PG 13.5 for cables with a diameter of 6.5÷11.5 mm. Flat glass 4 mm thick tempered and serigraphed. Ceramic lamp-holder fixed on components case.

| | | | |
|-----------------------|--------------------|-------------------------------------|--------------------|
| Application | External | IP degree | IP66 |
| Mechanical resistance | IK10 | Maximum surface exposed to the wind | 0.3 m ² |
| Tilt adjustable | +20° -20° | Weight (kg) | 13.8 |
| Colour | Graphite/Aluminium | Max lamp power | 400 W |
| Lamp holder | E40 | Optic | Cut-Off |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY



IP
IP66

IK
IK10

