





Street lighting with pole coupling (diameter 42÷76mm) and body in die-cast aluminium. The pole coupling base can be tilted for arm pole or head pole installation. Optic in 99.85% polished and anodised aluminium. Anti-aging silicone gasket. Anti-condensation device in felt. Removable polyamide case containing electrical components, equipped with handle to facilitate the operation time. Two poles power supply terminal in double insulation for max. 2.5 mm² cables; PG 13.5 for cables with a diameter of 6.5÷11.5 mm. Flat glass 4 mm thick tempered and serigraphed. Ceramic lamp-holder fixed on components case. Hard wiring cables 1-1.5 mm² in silicone with double insulation UG4G4.

Application	External	IP degree	IP66
Mechanical resistance	IK10	Insulation class	II
Maximum surface exposed to the wind	0.21 m ²	Minimum distance from the illuminated object	1 m
Tilt adjustable	+20° -20°	Weight (kg)	10.9
Colour	Graphite/Aluminium	Voltage	220-240 V - 50/60 Hz
Lamp	MT	Lamp power	60 W
Lamp current	0.65 A	Lamp holder	PGZ-12
Optical compartment protection	Flat glass	Driver type	EVG electronic reactor
Optic	Cut-Off - ULOR: 0%	Electrocod	244B

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP66

IK

IK10



0.21 m²

1 m

