




Street lighting with pole coupling (diameter 42÷76mm) and body in die-cast aluminium. The pole coupling base can be tilted for arm pole or head pole installation. Optic in 99.85% polished and anodised aluminium. Anti-aging silicone gasket. Anti-condensation device in felt. Removable polyamide case containing electrical components, equipped with handle to facilitate the operation time. Two poles power supply terminal in double insulation for max. 2.5 mm² cables; PG 13.5 for cables with a diameter of 6.5÷11.5 mm. Flat glass 4 mm thick tempered and serigraphed. Ceramic lamp-holder fixed on components case. Hard wiring cables 1-1.5 mm² in silicone with double insulation UG4G4. Bi-Power version equipped with dual output ballast and programmable electronic switching device.

Application	External	IP degree	IP66
Mechanical resistance	IK10	Insulation class	II
Maximum surface exposed to the wind	0.21 m ²	Minimum distance from the illuminated object	1 m
Tilt adjustable	+20° -20°	Weight (kg)	11.5
Colour	Graphite/Aluminium	Voltage	230 V - 50 Hz
Lamp	ST	Lamp power	70 W
Lamp current	1 A	Reduced power	50 W
Lamp holder	E27	Optical compartment protection	Flat glass
Power supply operation	Bi power	Optic	Cut-Off - ULOR: 0%
Electrocod	244B		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY



IP

IP66

IK

IK10



0.21 m²



1 m

