


Recessed device for modular ceiling 600x600mm. Steel sheet body painted white. Plastic prismatic diffuser. Mid Power LED lighting source.

| | | | |
|-----------------------|------------------------------------|-------------------------------------|-----------------------------|
| Application | Internal | Type | Stand alone |
| Installation | Flush mounting enclosures | Dimensions (mm) | 600 x 600 |
| Mechanical resistance | IK03 | Voltage | 220-240 V - 50/60 Hz |
| Voltage | 220/240 V - 50/60 Hz - Stand alone | System power | 31 W |
| Weight (kg) | 3.1 | Lamp | LED |
| Colour | White | Lumen output (lm) | 4250 |
| Optic | Diffused | IP degree | IP20 |
| Insulation class | I | Driver type | Constant Current Driver Led |
| Operating temperature | -25 +25 °C | UGR | <=19 |
| Warranty | 5 years | Colour temperature | 4000 K (CRI>80) |
| Type of light source | LED - Not replaceable | Efficiency class of integrated LEDs | A ÷ A++ |
| Electrocod | 2419 | LED Life Time (L80B50) | 50000 h |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IK
IK03



IP
IP20



CONSTANT
CURRENT
DRIVER



STANDARDS/APPROVALS

