Product Data Sheet

GWS2921D

On request

Modular recessed luminaire 300x1200 mm. Extruded aluminum frame with thermoplastic oven paint. Plastic diffuser with "fulllight" emission. MID Power LED Light Source.

Application	Internal	Installation	Flush mounting enclosures
Dimensions (mm)	300 x 1200	Mechanical resistance	IK04
Voltage	220/240 V - 50/60 Hz - DALI	System power	40 W
Weight (kg)	3.4	Lamp	LED
Colour	White	Lumen output (lm)	3450
IP degree	IP20 - IP40	Insulation class	II
Driver type	Driver Led	Operating temperature	-25 +40 °C
UGR	<=19	Warranty	5 years
Colour temperature	3000 K (CRI>80)	Efficiency class of integrated LEDs	A ÷ A++
Electrocod	2419	LED Life Time (L70B30)	50000 h

DIMENSIONAL

PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY

IK

IK04

IP

IP20 - IP40

STANDARDS/APPROVALS

Data, measures, designs and pictures are for information purpose only, last update 12/10/2024. They can be changed at any moment, therefore it is always ecommended to read the last updated version published on the website www.gewiss.com.Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at https://www.gewiss.com/it/en/company/landingpage/led-warranty. - 1 of 1