





Urban decorative in die-cast aluminum EN AB 46100 powder poliester painted after epoxy surface treatment and phosphochromating process, with lateral ventilation system by plastic grid. Recessed handle closing system and steel holding cable. External screw stainless steel AISI 316. Anti ageing silicone gasket. Double two poles safety knife for wires 2,5 mm<sup>2</sup>. PC holding components plate. Internal wiring with UG4G4 1mmq wires. Modular LED engines (2-4) with injected aluminum heat sink equipped with PMMA lenses. Pole fixing system provided with Gewiss bracket. It can be used up to 50 ° C of ambient temperature but with reduced currents as indicated in the Technical Manual.

Insulation class	II	Colour	Graphite grey
IP degree	IP66	Mechanical resistance	IK08 BODY - IK06 LENS
Voltage	220/240 V - 50/60 Hz - Bi-power with self-learning	Weight (kg)	9.5
Series	URBAN [O3]	Application	External
Number of modules	4 (4x16 LED)	Optic	Elliptical - ULOR: 0%
Maximum surface exposed to the wind	0.25 m <sup>2</sup>	Minimum distance from the illuminated object	1 m
Suitable for	Gewiss side brackets	System power	105 W
Lumen output (lm)	6610	Colour temperature	3500 K (CRI>85)
Voltage	220-240 V - 50/60 Hz	LED current	530mA
Power supply operation	Bi power	Warranty	5 years
Operating temperature	-25 +35 °C	Driver type	Constant Current Driver Led
Type of lamp	LED	Electrocod	244C
Photobiologic Risk	RG1/RG2 @ 20cm	Nominal flux (lm)	7540
LED Life Time (L80B10)	100000 h	LED Life Time (L90B20)	50000 h
Overvoltage resistance	Common mode: 8KV; Differential mode: 6KV		

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



### TECHNICAL SYMBOLOGY



IP

IP66

IK

IK08 BODY -  
IK06 LENS



INSTALLATION  
25 °C max  
min +35 °C



CONSTANT  
CURRENT  
DRIVER



0.25 m<sup>2</sup>



1 m



### STANDARDS/APPROVALS

