





Smart [4] is a series of LED indoor appliances suitable for the lighting of industries and sports facilities. It is available in HE (High Efficiency), HLO (High Lumen Output) and integrated DALI Emergency. Three different sizes available: 1M, 2M and 4M. The body is made of "Halogen-free" nylon loaded with grey glass fibre (RAL7035) with vent and anti-condensation device, heat dissipation device in aluminium alloy EN AB 44300. It is equipped with a dual optical system that includes a metallic reflector with ARRAY optics and a metallic reflector with UV stabilized PMMA lenses, with high efficiency, which allow a wide variety of light distributions 30°, 60°, 90°, Asymmetric and Elliptical. The version with through wiring has pre-wired mechanical and electrical connection components. Suspension, wall and projection appliances can be installed. It is available with three types of Colour Temperature (3000K / 4000K / 5700K), Color Rendering Index CRI>80 and two power supply options (ON/OFF or DALI).

GENERAL INFORMATION		OPTIC AND ILLUMINATING FEATURES	
Context	Logistics and industrial manufacturing lighting	Optic	Array
Luminaire Application	LED Industrial Reflector Internal	Unified Glare Rating	-
Unique digital code (Datamatrix)	Datamatrix	Lumen output (lm)	9900 (950 Em.)
Colour	Grey RAL 7035	Efficacy (lm/W)	155
Type of light source	LED	Colour temperature	5700 K
System power	64 W (+5W Emerg.)	Colour Rendering Index	CRI>80
LED Lifetime	L90B10(Tq25°C)>150.000h; L90B10 (Tq40°C)=140.000h	Standard Deviation Colour Matching	SDCM = 3
Weight (kg)	5	Photobiological Risk Class	RG0
Warranty	5 years	Standard	EN 60598-2-22 ; EN 60598-1 ; EN 60598-2-24
Stocking temperature	-40 +70 °C	ELETRICAL AND LIGHTING FEATURES	
Operating temperature	0 ÷ +40 °C	Supply voltage	220 - 240 V
MATERIALS		Rated frequency (Hz)	50/60 Hz
Body	PA6 "Halogen Free" loaded fibreglass	Driver	Included
Shield type	Tempered glass Thickness 4mm	Driver failure rate	F10 = 100.000h Tq25°C/50.000h Tq40°C
Optic	Metallized polycarbonate reflector	Overvoltage protection	DM 6 kV / CM 10 kV
Gasket	anti-aging silicone	Control System	1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h)
Locking Hook	-	INSTALLATION AND MAINTENANCE	
External screw	Stainless steel	Mounting and installation	Ceiling light - Suspension
Colour	Grey RAL 7035	Tilt	-
STANDARDS AND APPROVALS		Wiring	With GW connect watertight connector
Classification	-	Fixing	-
Device with reduced surface temperature	Yes	Light source replaceability	By professional
DIN 18032-3 certification	Available (under certain installation conditions)	Controlgear replaceability	By professional
IPEA	-	Driver Box	Built-in
Insulation class	I	Maximum surface exposed to the wind	0,140 m ²
IP degree	IP65		-
Mechanical resistance	IK08		-
Glow Wire Test	850 °C		-

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP
IP65

IK
IK08

GWT
850 °C



Product Data Sheet
GWS4124BA857

SMART [4]

STANDARDS/APPROVALS

