



Description Interruttore automatico scatolato

Code MSX 160c

Nombre de pôles 3P+N

Courant nominal 25 A

Déclencheur Elettromeccanico


ELECTRICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS		MECHANICAL CHARACTERISTICS	
Norme	IEC/EN 60947-2	Exécution	Fixe
Catégorie d'utilisation	A	DIN rail mounting	Si, tramite accessorio
Fréquence nominale (Hz)	50 / 60	Accessoriabile con comando motore	Non
Rated operating voltage (Ue)	525 Vac - 250 Vdc	Compatible interlock	-
Tension nominale tenue à l'impulsion (Uimp)	8 kV	Terminals supplied	Partie avant pour câbles FW
Catégorie de surtension	IV	Position de montage	Tout
Tension d'isolement (Ui)	690 V	Upline/downline power supply	Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	14.000 cicli
Magnetic regulation	Fisso - 600A	Mechanical life	20.000 cicli
Neutral protection	Non protetto	Température d'utilisation	-5°C +65°C
Total power loss	18.4 W	Température de stockage	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Poids (kg)	1
Rated short-time withstand current for 0,3s (Icw)	-	Largeur	100 mm
I _{dn} regulation	-	Hauteur	130 mm
DT regulation	-	Profondeur	68 mm

SERVICE BREAKING CAPACITY (ICU)

SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)	
220/240Vac	25 kA	220/240Vac	13 kA
400/415Vac	16 kA	400/415Vac	8 kA
440Vac	10 kA	440Vac	5 kA
525Vac	6 kA	525Vac	3 kA
690Vac	-	690Vac	-
250Vdc	13 kA	250Vdc	7 kA

DIMENSIONS





Fiche produit

GWD9011

Gamme MSX

NORMES ET HOMOLOGATIONS

