



A complete, versatile system of modular containers, perfectly integrable in the SYSTEM domestic range and able to meet the high protection installation requirements of the residential, commercial and industrial sectors. The 27 COMBI range is available both in the IP40 version and in watertight versions with IP55, IP65 and IP66 degree of protection, recommended for all outdoor applications which are subjected to extreme atmospheric conditions.

IP degree	IP65	Insulation class	II
Outer dim. LxHxD (mm)	55x106x45	Threshold adjustment	0 - 200 lux
Output contacts	1NO 16 A (AC1) 250 V ac	Glow Wire Test	650 °C
Thermo-pressure with ball	70 °C	Standard	EN 60669-2-1
Installation temperature	-30 +60 °C	Electrocod	0143

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Resistant

#### DIMENSIONAL

#### TECHNICAL SYMBOLOGY

**IP**

IP65



II

**GWT**

650 °C



70 °C

#### STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 18/10/2019

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice