



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and metal, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.


DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.

The series is completed with versions for board from 16 A to 800 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

Wyposażniki	Izolator obrotowy	Wersja	Z tablicy
Prąd znamionowy (A)	32	Liczba biegunów	3P
Zakres regulacji	87 - 145 mm	Liczba modułów EN 50022	4
Prąd w AC21A (415V)	32	Kolor gałki	Czerwony
Prąd w AC22A (415V)	32	Zamykany	TAK (maks. 3 blokady w trybie OFF)
Prąd w AC23A (415V)	32	Kabel przekrój	1-10 mm²

## DIMENSIONAL



## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 26/04/2024

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice