



The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

WEJŚCIE		-	Nr gniazda/wtyczki (Typ)	2 (gniazdo typu 2, z ?aluzj?)
Listwy zaciskowe	2 x (3 x 10 mm ²)		Aktywacja ?adowania	Bezpie?atny dost?p
Pr?d roboczy	64 A		HMI	Wy?wietlacz LED RGB i TFT
Moc ca?kowita	15 Kilowatt		??czno??	Nie
WYJŚCIE		-	INFORMACJE MECHANICZNE	-
Pr?d wyj?ciowe	230 V		Monta? i instalacja	Monta? na?cienny
Kolor	Szare, górna cz?? RAL 7011		Akumulatory maks.	7,4 kW per socket
Materia?	Arkusze blachy stalowej		Ochrona termiczno-magnetyczna	Obecnie niedost?pny
Obróbka zewn?trzna	Ochrona przed korozj? i graffiti		Typ ochrony ró?nicopr?dowej	Obecnie niedost?pny
Ochrona IP	IP55		Miernik zasilania	Obecnie niedost?pny
Odporno?? na wstrz?sy	IK10		Kontrola up?ywu DC	Obecnie niedost?pny
Temperatura pracy	-25 +50 °C		(Auto)restart zabezpiecze? elektrycznych	Nie
Dostosowania	Tak (przód)			

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

