



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and metal, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.

The series is completed with versions for board from 16 A to 800 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

Zakres regulacji	117-305mm (16-40A) - 144-337mm (63-80A)	Prąd znamionowy (A)	16
Do izolatora	16 A - 25 A - 32 A - 40 A - 63 A - 80 A	Zakres regulacji	90 - 160 mm
Akcesoria w zestawie	Zestaw uchwytów	Electrocod	1740



DIMENSIONAL

TECHNICAL SYMBOLOGY STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 28/04/2024

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice