




Wiring devices system characterized by its profile and shape inspired to the Chorus family feeling. Wide range of plates with an Italian design, articulated into two families, GEO and LUX cover plates, available in many materials and finishes. The range is available in three colors: glossy white, satin black, painted titanium and fits in 3x3 inches (1-gang) and 3x6 inches (2-gang) British Standard boxes. Range expandable thanks to the Chorus modular devices.

kategoria	Jednostka po??czeniowa z bezpiecznikiem	Opis	2P - 13 AX
Kolor	Bia??y	wyj??ciowe	250V ac
Moc znamionowa lamp LED 230V	150 W	Zaciski okablowania	Ze ?rub?
Norma	IEC 60669-1	Rezystancja przy napi?ciu probierczym	2000 V przy 50 Hz przez 1 minut?
Rezystancja izolacji	> 5 Momów	Twardo?? kulkowa	125 °C
Próba roz?arzonym drutem	850 °C	Uchwyt zacisku na trakcji kablowej	> 50 N
Zakres dokr?cenia zacisku przewody elastyczne (mm ²)	min. 1 - max. 2,5	Zakres dokr?cenia zacisku przewody sztywne (mm ²)	min. 1 - max. 2,5
Wyd?u?ona praca (liczba zmian po?o?enia)	40,000 przy In 250 V AC cos?=0,6	Ø min kabla	5 mm
Ø maks kabla	11 mm		

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

