


Smart plate can be used with Home Gateway for "CONNECTED SMART HOME" solutions. The EGO SMART plates integrate with the connected devices of the ChoruSmart system, they go beyond pure aesthetics and become an element of interaction with the user. The plates communicate with the other connected devices and, using RGB perimeter LED strips and a graphic display, can communicate operating statuses and any alarms detected by the smart functions that control the home to the user. The traditional EGO SMART and EGO plates can be used in the same system as they are designed to blend in perfectly.

Kolor	Złoty	Opis	3 zespoły
Do wspornika o kodzie	GW16803N	Układ zasilania	Za pośrednictwem jednego z odpowiednich podłączonych urządzeń zainstalowanych w nim lub za pośrednictwem dedykowanego zasilacza GWA1700
Norma	2014/35/EU, 2014/30/EU, 2011/65/EU + 2015/863, EN 62368-1, EN 55032, EN 55035, EN IEC 63000	Długość Temperatury	-5 ÷ +45 °C
Wilgotność względna (bez kondensacji)	Max 93%	Ochrona IP	IP20
Funkcje	Informacje o systemie/stanie z komunikatami na wyświetlaczu i powiadomieniami za pomocą pasków LED RGB.	Materiał	Lakierowany technopolimer
Wykończenie	Wykończenie nieprzezroczyste	Próba rozżarzoną drutem	650 °C
Twardość kulkowa	70 °C	Rodzina	EGO SMART
Interfejs użytkownika	Tablica wyposażona jest w wyświetlacz dot-matrix i paski LED RGB		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

GWT

650 °C



70 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 27/05/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice