




Complete system for the connection and distribution of LAN networks in residential and tertiary sector environments.

The range includes fibre optic solutions, wall panels, floor cabinets and copper wiring products.

The Data Center series provides all the products necessary to create a multi-service fibre optic infrastructure for residential buildings, in full compliance with all the indications dictated by the new CEI Guidelines 306-2 and Law 164/14.

kategoria	Złącze optyczne	Kolor kabla	Biały
Liczba światłowodów	1	Długość (mm)	1 m
Ø osłony	0,9 mm	Dla złączy	SC/APC - SC/APC
Klasyfikacja	G.657.A2 / B6_a2 Bend Insensitive	Ø rdzenia	9 µm
Ø okładziny	125 µm	Plaszcz zewnętrzny	LSZH
Kabel	Tight - OS2	Minimalny promień gięcia (dynamiczny)	25x średnica kabla
Minimalny promień gięcia (statyczny)	15x średnica kabla	Maksymalne tłumienie (@1310 nm / @1550 nm)	0.35 / 0.2 dB/Km
Długość TemperatURY	Od -20°C do +60°C		

### DIMENSIONAL



### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 23/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice