



The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

WEJŚCIE	-	Nr gniazda/wtyczki (Typ)	2 (gniazdo wandaloodporne typ 2 z ?aluzj?)
Listwy zaciskowe	2 x (5 x 10 mm ²)	Aktywacja ?adowania	Zarz?dzenie zdalne za po?rednictwem OCPP 1.6J
Pr?d roboczy	32 A	HMI	Wy?wietlacz LED RGB i TFT
Moc ca?kowita	22 Kilowatt	??czno??	LAN
WYJŚCIE	-	INFORMACJE MECHANICZNE	-
Pr?d wyj?ciowe	400 V	Monta? i instalacja	Monta? na?cienny
Kolor	Szare, górna cz?? RAL 7011	Akumulatory maks.	11 kW per socket
Materia?	Arkusz blachy stalowej	Ochrona termiczno-magnetyczna	Obecnie niedost?pny
Obróbka zewn?trzna	Ochrona przed korozj? i graffiti	Typ ochrony ró?nicopr?dowej	Obecnie niedost?pny
Ochrona IP	IP55	Miernik zasilania	Tak (typ MID)
Odporno?? na wstrz?sy	IK10	Kontrola up?ywu DC	Obecnie niedost?pny
Temperatura pracy	-25 +50 °C	(Auto)restart zabezpiecze? elektrycznych	Obecnie niedost?pny
Dostosowania	Tak (przód)		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

