


### ESALITE HB




Industrial LED lighting fixture made of die-cast EN AB 46100 aluminum with polyester powder coating. Correct lighting is provided by an optical system composed of different versions of lenses. Silicone gaskets, breathing and anti-condensation device in Goretex, waterproof connector for 1.5 mm<sup>2</sup> cables and stainless steel external screws. Integrated suspension fixing system thanks to a ring made directly in the die-cast aluminum. The die-cast aluminum structure guarantees optimal performance conditions both @ Ta25 ° and @ Ta50 ° thanks to specific thermal sizing tests. The correct heat dispersion inside ESALITE is guaranteed by the special passive heat sink with a very low copper content that offers high qualitative and quantitative performances.

Seria	Esalite HB - 12K	Zastosowanie	Wewnętrzny
Temperatura pracy	-30°C ÷ +50 °C	Ochrona IP	IP65
Odporność na wstrząsy	IK07	Mocowanie	-
Klasa Izolacji	I	Napięcie zasilające	220-240 V - 50/60 Hz
Masa (kg)	7.5	Electrocod	2444

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



### TECHNICAL SYMBOLOGY



**IP**

IP65

**IK**

IK07



### STANDARDS/APPROVALS

