



Watertight enclosure for emergency use and special applications with rail DIN. It is available in red RAL 3000 or grey RAL7035 colours. Thanks to the emergency hammer, available as an accessory, sealable mask and halogen free materials are ideally suited for applications in areas open to public.

Curent nominal (A)	125	Clasă izolație	II
Culoare	RAL 3000 Roșu	Dim. exterioare LxHxP (mm)	108x180x100
Clasă de protecție IP	IP55	Instalare	Perete
Material	Tehnopolimer	Cod IK	IK08
Tensiune nominală (V)	400	Glow Test conductori	650 °C
Temperatură de operare	-25 +60 °C	Tip de material	Fără halogen conform EN 60754-2
Electrocod	0321	Termo-presiune cu bilă	70 °C
Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Tensiune izolație	750 V
Putere disipabilă (W)	12	Nr. module EN 50022	4



DIMENSIONAL

TECHNICAL SYMBOLOGY



II

IP

IP55

IK

IK08

GWT

650 °C



-25 +60 °C

HF

Fără halogen
conform EN 60754-2



70 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 15/06/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice