Product Data Sheet

# DX51306

GW FIT Range




Systems of accessories for electrical installations used for residential, tertiary and industrial applications. The system consists of fasteners for pipes and cables, cable fittings, accessories for rigid pipes (RK Series) and flexible conduit (DF Series). The system include also a wide variety of cable ties (52FS Range) and terminal blocks (44 Range).

| | | | |
|---|---|---|---|
| Colour | Grey RAL 7035 | IP degree | - |
| Characteristics | 1 Impact insert included | For mounting holes Ø (mm) | 6 |
| Glow Wire Test | 750 °C | Operating temperature | -5 +60 °C |
| Type of material | Halogen-free in compliance with EN 60754-2 | Electrocod | 21221 |
| Standard | EN 61386-1 (when applicable) | | |

## DIMENSIONAL

8

1





## TECHNICAL SYMBOLOGY

IP

-

GWT


750 °C







## STANDARDS/APPROVALS




GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 13/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice