

Product Data Sheet

CH10701

domestic range

coordinatiun de Politiu S.p.A.
 Compagnia s.p.a. con sede in via
 +39 032 84 81 11 fax +39 032 84 84 08
 Via S. Chiara 20/01 - Bergamo - Italia
 GEWISS S.p.A. Via V. Lillo 1

last number 50102\5058
 sas@gewiss.com
 www.gewiss.com

and could be changed without previous notice
 only as informative purposes
 Data measures designed and are shown



Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The ChoruSmart modular devices are available in five colours, glossy white, satin white, natural beige, satin black and lacquered titanium and in various sizes from 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the ChoruSmart range of plates.

Category	Relay	Output contacts	1NO/NC 10 A (AC1)/2 A (AC15) 250 V ac
Type	Monostable relay	Colour	Satin black
Description	Monostable relay	No. of poles	1P
Voltage	230 V ac	Standard	EN 60669-1 / EN 60669-2-2
Frequency	50/60 Hz	Resistance at test voltage	2000 V at 50 Hz for 1 minute
Insulation resistance	> 5 MOhm	Wiring terminals	With screw
Prolonged operation switch (no. of position changes)	40.000 at In 250 V ac cosφ=0,6	Thermo-pressure with ball	125 °C
Glow Wire Test	850 °C	Terminal grip on cable traction	> 50 N
Terminal tightening capacity stranded cables (mm ²)	min. 1 - max. 2x4	Terminal tightening capacity solid cables (mm ²)	min. 1 - max. 2x2,5
No. modules	1	Material	Technopolymer
Electrocod	140		

DIMENSIONAL