# Product Data Sheet

# GW21265


SYSTEM BLACK - Domestic range





The System modular devices allow the creation of infinite combinations of devices and plates, through a complete range that covers all design, functional and installation needs. Colours and finishes: satin black, elegant and classy. Ideal for flush-mounted solutions (for rectangular or square boxes), surface-mounted solutions and special applications. The range includes control units, socket-outlets, breakers, indicators, connectors and devices for the control, safety and comfort of your home

| | | | |
|---|---|---|---|
| Category | Socket-Outlet | Description | 2P+E - 16 A |
| Colour | Black | Voltage | 250 V ac |
| Earth pit | - | Standard | German |
| Characteristics | With safety shields | For plug pins | Ø 4.8 mm |
| Wiring terminals | With screw | Standard | IEC 60884-1; UNE 20315-1-1; UNE 20315-1-2 |
| Resistance at test voltage | 2000 V at 50 Hz for 1 minute | Prolonged operation switch (no.of position changes) | 10.000 at In 250 V ac cosφ=0.8 |
| Thermo-pressure with ball | 125 °C | Glow Wire Test | 850 °C |
| Terminal grip on cable traction | > 50 N | Terminal tightening capacity stranded cables (mm²) | min. 0.75 - max. 2x4 |
| Terminal tightening capacity solid cables (mm²) | min. 0.5 - max. 2x2.5 | No. SYSTEM modules | 2 |
| Material | Technopolymer | Electrocod | 0131 |

## DIMENSIONAL




## TECHNICAL SYMBOLOGY




## STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 02/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice